



Natural Woods.
Attractive Styles.



WALL PANELING



WHAT MAKES REAL HARDWOOD PANELING BETTER?

States hardwood panels are as resilient as they are beautiful. Veneered construction finished with exceptionally hard, ultraviolet cured top-coats withstand years of abuse.

Why is hardwood paneling better?

First of all, it's real. And for some people that alone makes all the difference.

Because it's real, it's unique. No two panels of real wood are ever identical.

Real wood paneling offers the discerning buyer subtle variations of grain and color.

Real wood veneers age, growing naturally warmer and richer with the passage of time.

Real wood paneling is simple to maintain.

And real wood comes with the rugged durability of nature born to it. Because of this, it resists scuffing and staining with amazing stubbornness.

Hardwood paneling lasts longer.

Lastly, should it ever be damaged, real wood paneling can be repaired whereas prints and overlays usually must be replaced.



American Cherry



Liberty Oak



French Brushed Oak



Stamford Finished Oak



Aged Antique Birch



Finished Birch



Carmalized Bamboo



Natural Bamboo



Stamford Unfinished Oak

The Warmth and Beauty of Natural Woods.

Additional Styles Available

States offers more than forty species, patterns and colors of wall paneling products. Paneling is 48" wide by 96" high.

Hardwood Options

Distinctive panels in a mix of species that range from traditional to modern. Rich colors combined

with multiple groove options provide choices to fit any home or corporate setting. Please visit StatesInd.com

for specifics on available options or to inquire about custom choices.



Alpine Cedar



MDF Raw



MDF Primed 1.5"



MDF Great White



Aromatic Cedar



MDF Oyster White



MDF Designer White



Rustic Cedar



MDF Designer White 3"



MDF Primed 3"

Additional Styles Available

States offers more than forty species, patterns and colors of wall paneling products. Paneling is 48" wide by 96" high. Thickness is 5/32", 1/4" or 3/8" depending on the species and pattern selected. Multiple groove types and patterns are available.



Natural Unfinished Options

Natural grains and knot textures combine to create ambience, warmth and security. Aromatic Cedar is often used to line closets and storage chests.

Finished or Unfinished Beaded Panels

Beaded panels are versatile, making them a popular choice, especially as wainscot. Unfinished

beaded panels can be painted or stained to match existing millwork. This option allows for control of the ambient effects of both natural and artificial lighting.

All States Industries paneling is made from natural wood veneers. States finished wall panels feature NOVA® ultraviolet cured top-coats which are impervious to household stains and solvents. States Industries paneling is made in America by American craftsmen.



States wall panels have no added formaldehyde. Most can be ordered FSC® certified.



FSC
www.fsc.org
FSC C003370

The mark of responsible forestry

INSTALLATION TIPS

Detailed installation instructions are available from your panel supplier. The following tips are specific to natural wood panels and should be observed in addition to general installation instructions.

Prearrange Your Panels

States panels are made with natural wood veneers. Each panel is a distinctive blend of color and grain variations. Prior to installation, you should stand the

panels upright around the room to achieve the most pleasing effect. Note that there is a top and bottom to each panel. Once you have determined placement, number the panels to avoid confusion.

Acclimate New Panels

Panels should be stored in the room where they will be installed, at normal temperature for a period of 24 hours. Separate the panels with a spacer to allow air to circulate around

them. This procedure allows the wood to adjust to the humidity and temperature, and prevents any shrinkage or expansion after installation.

Allow Adequate Clearance

There is a tendency to fit panels as tightly as possible. While this is understandable, it is not a good practice. Butt panels snugly along their sides, but allow a minimum of 1/8" space at the top and bottom. This space will be covered

by moulding, and will not be visible. Spacing allows the panel and the wall to expand and contract with changes in temperature and humidity.



States Industries, LLC
29545 Enid Road, East
PO Box 41150
Eugene, OR 97404

888.786.5247
StatesInd.com

